

## 美国理想工业 连接器与导线匹配关系速查表（扭接式）

线径范围 (mm <sup>2</sup> )		2x0.3	2x0.5	2x0.6	2x0.75	2x1.5	3x1.5	2x2.5	3x2.5	4x2.5	3x4.0	4x4.0	5x4.0	2x6.0 +2x2.5	4x6.0
型号	外形														
Zhong-Twist™ 115™			●	●	●	●	●	●	●	●	●				
IDEAL 71B		●	●	●	●	●									
IDEAL 72B		●	●	●	●	●									
IDEAL 73B				●	●	●	●	●							
IDEAL 74B					●	●	●	●	●						
IDEAL 76B							●	●	●	●					
IDEAL 59B			●	●	●	●	●	●	●						
IDEAL 451					●	●	●	●	●						
IDEAL 452					●	●	●	●	●	●	●	●			
IDEAL 454									●	●	●	●	●	●	●
IDEALL 340		●	●	●	●	●	●	●							
IDEALL 341			●	●	●	●	●	●	●	●	●				
IDEAL 342									●	●	●	●	●	●	
IDEAL 344					●	●	●	●	●	●	●	●			
IDEAL 60				●	●	●	●	●	●	●					
IDEAL 61			●	●	●	●	●	●	●						
IDEAL 62					●	●	●	●	●	●	●				
IDEAL 63							●	●	●	●	●	●	●		
IDEAL 64				●	●	●	●	●	●	●					
IDEAL 66									●	●	●	●	●	●	●

## 美国理想工业 连接器与导线匹配关系速查表（插接式）

插接式导线连接器		线芯形式	线径范围 (mm <sup>2</sup> )						
型号	外形		0.5	0.75	1.5	2.5	4.0	6.0	
IDEAL32 IDEAL33 IDEAL34		单股	●	●	●	●	●		
		多股	≤19股			●	●	●	
			≤7股						
		多股搪锡	≤19股		●	●			
IDEAL87 IDEAL88 IDEAL90		单股	●	●	●	●			
		多股	≤19股		●	●			
			≤7股		●				
		多股搪锡	≤19股			●	●		
			≤16股		●				
IDEAL39		单股			●	●	●	●	
		多股	≤19股				●	●	
		多股搪锡	≤19股			●	●	●	●